

## CLAIMS

Sub  
a1

1. A light sensor comprising:  
a light emitter;  
a light receiver for receiving light emitted from said light emitter; and  
a light guide for taking in the light emitted from the light emitter, reflecting the taken-in light at a reflection portion provided on a part thereof, and ejecting the light toward the light receiver, wherein the light receiver and the light guide are disposed so as to be opposed to each other with an appropriate space in between, and entry of an object into said space is detected based on the light received by the light receiver.

2. The light sensor according to Claim 1, wherein the light guide in a plate shape, which has the reflection portion disposed on one plane thereof, takes in the light through one end face thereof, reflects the taken-in light at the reflection portion, and ejects the reflected light from the other plane thereof.

3. The light sensor according to Claim 2, wherein the reflection portion has a groove shape.

4. A light sensor comprising:  
a light emitter;

a light receiver for receiving light emitted from said light emitter and reflected at a reflective object; and

a light guide for taking in the light emitted from the light emitter, reflecting the taken-in light at a reflection portion provided on a part thereof, and ejecting the light,

wherein the light receiver receives the light ejected from the light guide and reflected at the reflective object, and a position of said reflective object is detected based on the light received by the light receiver.

5. The light sensor according to Claim 4, wherein the light guide in a plate shape, which has the reflection portion disposed on one plane thereof, takes in the light through one end face thereof, reflects the taken-in light at the reflection portion, and ejects the reflected light from the other plane thereof.

6. The light sensor according to Claim 5, wherein the reflection portion has a groove shape.

7. A light sensor comprising:

a light emitter;

a light receiver for receiving light emitted from said light emitter; and

a light guide for taking in the light emitted from the light emitter, reflecting the taken-in light at a reflection portion provided

Sub  
a1

Sub  
a1

on a part thereof, and ejecting the light toward the light receiver,  
 wherein the light emitter and the light guide are disposed  
 so as to be opposed to each other with an appropriate space in  
 between, and entry of an object into said space is detected based on  
 the light received by the light receiver.

8. The light sensor according to Claim 7, wherein the light  
 guide in a plate shape, which has the reflection portion disposed on  
 one plane thereof, takes in the light through one end face thereof,  
 reflects the taken-in light at the reflection portion, and ejects the  
 reflected light from the other plane thereof.

9. The light sensor according to Claim 8, wherein the  
 reflection portion has a groove shape.

10. A light sensor comprising:

a light emitter;

a light receiver for receiving light emitted from said light  
 emitter;

a first light guide for taking in the light emitted from the  
 light emitter, reflecting the taken-in light at a first reflection  
 portion provided on a part thereof, and ejecting the light; and

a second light guide for taking in the light ejected from said  
 first guiding body, reflecting the taken-in light at a second reflection  
 portion provided on a part thereof, and ejecting the light toward the

Sus  
 21

2000-01-01

light receiver,

wherein the first light guide and the second light guide are disposed so as to be opposed to each other with an appropriate space in between, and entry of an object into said space is detected based on the light received by the light receiver.

11. The light sensor according to Claim 10, wherein the first light guide in a plate shape, which has the first reflection portion disposed on one plane thereof, takes in the light through one end face thereof, reflects the taken-in light at the reflection portion, and ejects the reflected light from the other plane thereof.

12. The light sensor according to Claim 11, wherein the first reflection portion has a groove shape.

13. The light sensor according to Claim 12, wherein the second light guide in a plate shape, which has the second reflection portion disposed on one plane thereof, takes in the light through one end face thereof, reflects the taken-in light at the reflection portion, and ejects the reflected light from the other plane thereof.

14. The light sensor according to Claim 13, wherein the second reflection portion has a groove shape.

15. The light sensor according to Claim 10, wherein the

second light guide in a plate shape, which has the second reflection portion disposed on one plane thereof, takes in the light through one end face thereof, reflects the taken-in light at the reflection portion, and ejects the reflected light from the other plane thereof.

16. The light sensor according to Claim 15, wherein the second reflection portion has a groove shape.